

## *Apt*

### Table des matières

1	Dépôts	1
2	Paquets locaux	1
3	compilation du noyau	2

### 1 Dépôts

- */etc/apt/sources.list*

```
#
# deb cdrom:[Debian GNU/Linux 4.0 r4a _Etch_ - Official i386 CD Binary-1 20080803-21:07]/ etch
# deb-src ...

#deb http://security.debian.org/ etch/updates main contrib
#deb http://ftp.fr.debian.org/debian etch main contrib non-free

deb http://security.debian.org/ lenny/updates main contrib
deb http://ftp.fr.debian.org/debian lenny main contrib non-free

# (pour faire #apt-get install flashplugin-nonfree debian-backports-keyring)
deb http://www.backports.org/debian etch-backports main contrib
```

- */etc/apt/apt.conf.d/00release*

```
APT::Default-Release "lenny";
```

- Apt-file :

```
# apt-get install apt-file
# apt-file update
```

### 2 Paquets locaux

Maj de l'index.

```
$ mkdir /opt/debs
$ cp hot-babe_0.2.1-1_i386.deb /opt/debs/
$ cd /opt
$ dpkg-scanpackages debs /dev/null | gzip > debs/Packages.gz
```

Pointer sur l'index : fichier */etc/apt/sources.list*

```
### les paquetages ramenés à la main
deb file:/opt debs/
```

Installer les paquets :

```
# apt-get update
# apt-get install hot-babe
```

